



## Zebra ZT510 label printer Thermal transfer 300 x 300 DPI 305 mm/sec Wired & Wireless Ethernet LAN Wi-Fi Bluetooth

**Brand :** Zebra

**Product code:** ZT51043-T01A000Z

**Product name :** ZT510

Thermal Transfer/Direct Thermal Industrial Printer, 4-Inch Max Print Width, 300 dpi Resolution, USB 2.0, Serial RS-232, Ethernet, Bluetooth LE Connectivity, Wi-Fi, Includes: Tear Bar, US Cord  
Zebra ZT510. Print technology: Thermal transfer, Maximum resolution: 300 x 300 DPI, Print speed: 305 mm/sec. Connectivity technology: Wired & Wireless, Ethernet LAN, Wi-Fi, Bluetooth, USB port. Product colour: Grey



| Printing                    |                                                                                                               | Performance                       |                                                                                                                                                                           |
|-----------------------------|---------------------------------------------------------------------------------------------------------------|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Print technology *          | Thermal transfer                                                                                              | Certification                     | EC 60950, EN 55022 Class B, EN 55024, EN 61000-3-2, EN 61000-3-3 cTUVus, CE Marking, FCC-B, ICES-003, VCCI, C-Tick, NOM, S-Mark (Arg), CCC, CU, BSMI, KCC, SABS, IN Metro |
| Colour *                    | ✗                                                                                                             |                                   |                                                                                                                                                                           |
| Maximum resolution *        | 300 x 300 DPI                                                                                                 |                                   |                                                                                                                                                                           |
| Print speed *               | 305 mm/sec                                                                                                    |                                   |                                                                                                                                                                           |
| Paper handling              |                                                                                                               | Design                            |                                                                                                                                                                           |
| Ribbon width                | 11 cm                                                                                                         | Product colour *                  | Grey                                                                                                                                                                      |
| Ribbon length               | 450 m                                                                                                         | Built-in display                  | ✓                                                                                                                                                                         |
| Maximum label width         | 11.4 cm                                                                                                       | Display *                         | LCD                                                                                                                                                                       |
| Maximum roll diameter       | 20.3 cm                                                                                                       | Display diagonal                  | 10.2 cm (4")                                                                                                                                                              |
| Media thickness             | 0.076 x 0.305 mm                                                                                              | Power                             |                                                                                                                                                                           |
| Ports & interfaces          |                                                                                                               | Power consumption (printing)      | 250 W                                                                                                                                                                     |
| Connectivity technology *   | Wired & Wireless                                                                                              | AC input voltage                  | 90 - 265 V                                                                                                                                                                |
| Ethernet LAN *              | ✓                                                                                                             | AC input frequency                | 47 - 63 Hz                                                                                                                                                                |
| Wi-Fi *                     | ✓                                                                                                             | Operational conditions            |                                                                                                                                                                           |
| Bluetooth                   | ✓                                                                                                             | Operating relative humidity (H-H) | 20 - 85%                                                                                                                                                                  |
| Bluetooth Low Energy (BLE)  | ✓                                                                                                             | Storage relative humidity (H-H)   | 20 - 85%                                                                                                                                                                  |
| USB port *                  | ✓                                                                                                             | Operating temperature (T-T)       | 5 - 40 °C                                                                                                                                                                 |
| USB 2.0 ports quantity      | 1                                                                                                             | Storage temperature (T-T)         | -30 - 60 °C                                                                                                                                                               |
| RS-232 ports                | 1                                                                                                             | Weight & dimensions               |                                                                                                                                                                           |
| Performance                 |                                                                                                               | Width                             | 268.2 mm                                                                                                                                                                  |
| Internal memory             | 512 MB                                                                                                        | Depth                             | 512.3 mm                                                                                                                                                                  |
| Flash memory                | 2048 MB                                                                                                       | Height                            | 395.7 mm                                                                                                                                                                  |
| Built-in barcodes           | Code 11, Code 128 (A/B/C), Code 39, Code 93, Data Matrix, EAN13, EAN8, MaxiCode, QR Code, TLC39, UPC-A, UPC-E | Weight                            | 22.7 kg                                                                                                                                                                   |
| Technical details           |                                                                                                               |                                   |                                                                                                                                                                           |
| Sustainability certificates |                                                                                                               | ENERGY STAR                       |                                                                                                                                                                           |

**Other features**

|                |   |
|----------------|---|
| Navigation key | ✓ |
|----------------|---|

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.