



## Zebra MP7001 Built-in bar code reader 1D/2D CMOS Black, Stainless steel



**Brand :** Zebra

**Product code:** MP7001-LNSLM00CM

**Product name :** MP7001

MP7000 Multi-Plane Scanner, Long, Single Interval Scale, Multiple CMOS Array Imager 1D/2D, USB/RS-232/IBM RS-485

Zebra MP7001. Type: Built-in bar code reader, Scanner type: 1D/2D, Sensor type: CMOS. Connectivity technology: Wired, Standard interfaces: RS-232, RS-485, USB. Product colour: Black, Stainless steel, Keys quantity: 4 keys, Image formats supported: BMP, JPEG. Power source type: AC, RS-232, USB, Power consumption (typical): 5.5 W, Power consumption (standby): 3 W. Weight: 8 kg, Width: 292 mm, Depth: 102 mm

| Scanning                                   |                                                                                                                                                                                                                                           | Power                             |                 |
|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-----------------|
| Type *                                     | Built-in bar code reader                                                                                                                                                                                                                  | Power source type *               | AC, RS-232, USB |
| Scanner type *                             | 1D/2D                                                                                                                                                                                                                                     | Power consumption (typical)       | 5.5 W           |
| Sensor type *                              | CMOS                                                                                                                                                                                                                                      | Power consumption (standby)       | 3 W             |
| Linear (1D) barcodes supported *           | Codabar, Code 128, Code 32, Code 39, Code 93, Discrete 2 of 5, EAN 128, EAN-13, EAN-8, GS1 DataBar, GS1 DataBar Expanded, GS1 DataBar Omnidirectional, GS1 Databar Limited, Interleaved 2 of 5, JAN, MSI, Plessey, Trioptic, UPC-A, UPC-E | Input voltage                     | 90 - 264 V      |
|                                            |                                                                                                                                                                                                                                           | Input frequency                   | 47 - 63 Hz      |
| 2D (matrix & stacked) barcodes supported * | Aztec Code, Data Matrix, Han Xin, Micro QR Code, MicroPDF417, PDF417, QR Code                                                                                                                                                             | Weight & dimensions               |                 |
|                                            |                                                                                                                                                                                                                                           | Width                             | 292 mm          |
|                                            |                                                                                                                                                                                                                                           | Depth                             | 102 mm          |
|                                            |                                                                                                                                                                                                                                           | Height                            | 128 mm          |
|                                            |                                                                                                                                                                                                                                           | Weight *                          | 8 kg            |
| Ports & interfaces                         |                                                                                                                                                                                                                                           | Operational conditions            |                 |
| Connectivity technology *                  | Wired                                                                                                                                                                                                                                     | Operating temperature (T-T)       | 0 - 40 °C       |
| Standard interfaces *                      | RS-232, RS-485, USB                                                                                                                                                                                                                       | Storage temperature (T-T)         | -40 - 70 °C     |
|                                            |                                                                                                                                                                                                                                           | Operating relative humidity (H-H) | 20 - 95%        |
| Performance                                |                                                                                                                                                                                                                                           |                                   |                 |
| Keys quantity                              | 4 keys                                                                                                                                                                                                                                    |                                   |                 |
| LED indicators                             | ✓                                                                                                                                                                                                                                         |                                   |                 |
| Buzzer                                     | ✓                                                                                                                                                                                                                                         |                                   |                 |
| Image formats supported                    | BMP, JPEG                                                                                                                                                                                                                                 |                                   |                 |
| Product colour *                           | Black, Stainless steel                                                                                                                                                                                                                    |                                   |                 |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.