



## Zebra GX420d label printer Direct thermal 203 x 203 DPI 152 mm/sec Wired

**Brand :** Zebra

**Product code:** GX42-202410-000

**Product name :** GX420d



GX420d - 203dpi, DT, USB 1.1, Serial, Fast Ethernet, 1200g, Black

Zebra GX420d. Print technology: Direct thermal, Maximum resolution: 203 x 203 DPI, Print speed: 152 mm/sec. Connectivity technology: Wired. Supported paper width: 104 mm. Product colour: Black

| Printing                         |                                                                                | Performance                       |                                                                                                                                                                                         |
|----------------------------------|--------------------------------------------------------------------------------|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Print technology *               | Direct thermal                                                                 | Certification                     | -FCC Part 15, -Subpart 15, - VCCI, - C-Tick, -EN55022 Class-B, - EN6100-3-2, -EN6100-3-3, - EN55024, -CCC, -CB Scheme IEC 60950: 1991 +A1 +A2 + A3 +A4, - TUV NRTL, -IRAM, -NOM, -AAMI. |
| Maximum resolution *             | 203 x 203 DPI                                                                  |                                   |                                                                                                                                                                                         |
| Print speed *                    | 152 mm/sec                                                                     |                                   |                                                                                                                                                                                         |
| Paper handling                   |                                                                                | Design                            |                                                                                                                                                                                         |
| Maximum roll diameter            | 12.7 cm                                                                        | Product colour *                  | Black                                                                                                                                                                                   |
| Media thickness                  | 0.08 - 0.2 mm                                                                  |                                   |                                                                                                                                                                                         |
| Media thickness (imperial)       | 0.003 - 0.0075"                                                                | Power                             |                                                                                                                                                                                         |
| Supported paper width            | 104 mm                                                                         | Power requirements                | 100-240V, 50-60Hz                                                                                                                                                                       |
| Supported paper width (imperial) | 4.09"                                                                          |                                   |                                                                                                                                                                                         |
| Maximum media length             | 99.1 cm                                                                        | Operational conditions            |                                                                                                                                                                                         |
| Maximum media length (imperial)  | 39"                                                                            | Operating relative humidity (H-H) | 10 - 90%                                                                                                                                                                                |
| Ports & interfaces               |                                                                                | Storage relative humidity (H-H)   | 5 - 95%                                                                                                                                                                                 |
| Connectivity technology *        | Wired                                                                          | Operating temperature (T-T)       | 40 - 105 °F                                                                                                                                                                             |
| RS-232 ports                     | 1                                                                              | Operating temperature (T-T)       | 5 - 41 °C                                                                                                                                                                               |
| RS-232 interface                 | ✓                                                                              | Storage temperature (T-T)         | -40 - 60 °C                                                                                                                                                                             |
| USB 1.1 ports quantity           | 1                                                                              | Storage temperature (T-T)         | -40 - 140 °F                                                                                                                                                                            |
| Standard interfaces              | Ethernet                                                                       | Weight & dimensions               |                                                                                                                                                                                         |
| Optional connectivity            | Bluetooth                                                                      | Width                             | 171 mm                                                                                                                                                                                  |
| Performance                      |                                                                                | Depth                             | 209 mm                                                                                                                                                                                  |
| Internal memory                  | 8 MB                                                                           | Height                            | 152 mm                                                                                                                                                                                  |
| Flash memory                     | 4 MB                                                                           | Weight                            | 1.2 kg                                                                                                                                                                                  |
| Built-in barcodes                | EAN128, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, Matrix 2/5, UPC-A, UPC-E | Packaging data                    |                                                                                                                                                                                         |
|                                  |                                                                                | Package weight                    | 3.2 kg                                                                                                                                                                                  |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.