



Zebra LP 2844 label printer Direct thermal 203 102 mm/sec Wired

Brand : Zebra

Product code: 2844-20300-0031

Product name : LP 2844

LP 2844 - DT, 203dpi, RS232 Serial, Usb, Parallel, Real-Time Clock

[Zebra LP 2844 label printer Direct thermal 203 102 mm/sec Wired:](#)

The direct thermal LP 2844 bar code label printer is ideal for applications requiring a space-saving, desktop-size, 4.09" (104 mm) printer. This user-friendly printer delivers optimal performance in today's on-demand desktop labeling applications. The LP 2844 has a sturdy construction with a double-walled ABS casing.

The LP 2844 integrates easily into a variety of printing applications, including shipping and receiving, inventory control, healthcare, and medical laboratories, transportation and logistics, and e-commerce postage. Serial, parallel, and USB interfaces make this flexible, reliable, and affordable printer a smart investment.

Zebra LP 2844. Print technology: Direct thermal, Maximum resolution: 203, Print speed: 102 mm/sec. Connectivity technology: Wired. Supported paper width: 25.4 - 108 mm

Printing		Ports & interfaces	
Print technology *	Direct thermal	Optional connectivity	Ethernet, Parallel, Serial (RS-232), USB 2.0
Maximum resolution *	203		
Print speed *	102 mm/sec		
Paper handling		Performance	
Maximum label width	10.4 cm	Internal memory	0.25 MB
Maximum label length	0.279 m	Flash memory	0.5 MB
Maximum roll diameter	12.7 cm	Built-in barcodes	1D, 2D, EAN13, EAN8, Interleaved 2/5, POSTNET, UPC-A, UPC-E
Media thickness	0.08 - 0.18 mm	Certification	UL, FCC, VCCI/PSE, C-TICK, CSA, NOM, CE, CCC/SRRC, GOST-R
Media thickness (imperial)	0.003 - 0.007"		
Supported paper width	25.4 - 108 mm	System requirements	
Supported paper width (imperial)	1 - 4.25"	Compatible operating systems	Windows 95, 98, Me, NT4.0, NT2000, XP
Maximum media length	27.9 cm	Operational conditions	
Maximum media length (imperial)	11"	Operating relative humidity (H-H)	10 - 90%
Core diameter	3.81 cm	Storage relative humidity (H-H)	5 - 95%
Ports & interfaces		Operating temperature (T-T)	40 - 105 °F
Connectivity technology *	Wired	Operating temperature (T-T)	5 - 41 °C
Parallel ports quantity	1	Storage temperature (T-T)	-40 - 60 °C
RS-232 ports	1	Weight & dimensions	
RS-232 interface	✓	Width	201 mm
		Depth	238 mm
		Height	170 mm
		Weight	1.4 kg

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.