



Zebra TLP 2824 Plus label printer Direct thermal / Thermal transfer 203 102 mm/sec Wired

Brand : Zebra

Product code: 282P-101110-000

Product name : TLP 2824 Plus



TLP 2824 Plus - DT/TT, 203dpi, Usb, Serial

Zebra TLP 2824 Plus label printer Direct thermal / Thermal transfer 203 102 mm/sec Wired:

The ultra-compact TLP 2824 Plus™ bar code label printer, for print widths up to 2.2 inches/56 mm, brings powerful performance to applications requiring both direct thermal and thermal transfer printing. It includes a 32-bit RISC processor for faster formatting and first label out, an auto-sensing serial port, and co-resident EPL and ZPL programming languages. Available options include additional memory, 10/100 Ethernet, label peeler, and receipt/label cutter.

Its ease of use—including Zebra Setup Utilities software for simple setup, OpenACCESS™ design and clear media window for simple media loading and monitoring, and an instant reset button—results in increased workplace efficiency. Offering flexible connectivity and options, the TLP 2824 Plus fits easily into a variety of applications.

Printing		Ports & interfaces	
Print technology *	Direct thermal / Thermal transfer	Optional connectivity	Ethernet, Parallel, Serial (RS-232), USB 2.0
Maximum resolution *	203	Performance	
Print speed *	102 mm/sec	Internal memory	8 MB
Paper handling		Flash memory	4 MB
Ribbon width	5.8 cm	Built-in barcodes	1D, 2D, CODABAR (NW-7), EAN13, EAN8, Interleaved 2/5, POSTNET, UPC-A, UPC-E
Ribbon length	74 m	Certification	FCC, VCCI, C-TICK, UL, NOM, CE, IRAM, AAMI
Maximum label width	5.6 cm	Power	
Maximum label length	0.991 m	Power requirements	100-240 VAC, 50-60 Hz
Maximum roll diameter	12.7 cm	System requirements	
Media thickness	0.08 - 0.18 mm	Compatible operating systems	Windows 95, 98, Me, NT4.0, NT2000, XP
Media thickness (imperial)	0.003 - 0.007"	Operational conditions	
Supported paper width	25.4 - 60 mm	Operating relative humidity (H-H)	10 - 90%
Supported paper width (imperial)	1 - 2.36"	Storage relative humidity (H-H)	5 - 95%
Maximum media length	99.1 cm	Operating temperature (T-T)	40 - 105 °F
Maximum media length (imperial)	39"	Operating temperature (T-T)	5 - 41 °C
Core diameter	3.81 cm	Storage temperature (T-T)	-40 - 60 °C
Ports & interfaces		Weight & dimensions	
Connectivity technology *	Wired	Width	135 mm
Parallel ports quantity	1	Depth	241 mm
RS-232 ports	1	Height	178 mm
RS-232 interface	✓	Weight	1.6 kg

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.