



## Zebra LI2208 Handheld bar code reader 1D Linear White

**Brand :** Zebra

**Product code:** LI2208-SR6U2100AZN

**Product name :** LI2208



547 scans/s, 617nm LED, USB, IP42, 140g

Zebra LI2208. Type: Handheld bar code reader, Scanner type: 1D, Sensor type: Linear. Connectivity technology: Wired, Standard interfaces: USB, Cable length: 2.1 m. Product colour: White, International Protection (IP) code: IP42, Certification: EMC FCC Part 15 Class B, ICES 003 Class B, IEC 60601-1-2 Environmental RoHS Directive 2002/95/EEC..... Power source type: DC, Input voltage: 5 V, Power consumption: 165 mA. Weight: 140 g, Width: 67 mm, Depth: 99 mm

| Scanning                           |                                                         | Performance         |                                                              |        |
|------------------------------------|---------------------------------------------------------|---------------------|--------------------------------------------------------------|--------|
| Type *                             | Handheld bar code reader                                | Certification       | EMC FCC Part 15 Class B, ICES 003 Class B, IEC 60601-1-2     |        |
| Scanner type *                     | 1D                                                      |                     | Environmental RoHS Directive                                 |        |
| Sensor type *                      | Linear                                                  |                     | 2002/95/EEC Electrical Safety C22.2                          |        |
| Linear (1D) barcodes supported *   | Code 11, Code 128, Code 39, Code 93, EAN-13, EAN-8, JAN |                     | No. 60950-1, EN 60950-1, IEC 60950-1, UL 60950-1 LED Class 1 |        |
| Read rate (max)                    | 547 reads/s                                             |                     |                                                              |        |
| Light levels (direct sunlight)     | 0 - 108000 lx                                           | Power               |                                                              |        |
| Wavelength                         | 617 nm                                                  |                     | Power source type *                                          | DC     |
| Pitch reading angle                | -45 - 45°                                               |                     | Input voltage                                                | 5 V    |
|                                    |                                                         |                     | Power consumption                                            | 165 mA |
| Ports & interfaces                 |                                                         | Weight & dimensions |                                                              |        |
| Connectivity technology *          | Wired                                                   | Width               | 67 mm                                                        |        |
| Standard interfaces *              | USB                                                     | Depth               | 99 mm                                                        |        |
| Cable length                       | 2.1 m                                                   | Height              | 160 mm                                                       |        |
| Performance                        |                                                         | Weight *            | 140 g                                                        |        |
| International Protection (IP) code | IP42                                                    | Packaging data      |                                                              |        |
| Product colour *                   | White                                                   |                     | Cables included                                              | USB    |
| Operational conditions             |                                                         |                     |                                                              |        |
| Operating temperature (T-T)        |                                                         | 0 - 50 °C           |                                                              |        |
| Storage temperature (T-T)          |                                                         | -40 - 70 °C         |                                                              |        |
| Operating relative humidity (H-H)  |                                                         | 5 - 95%             |                                                              |        |
| Technical details                  |                                                         |                     |                                                              |        |
| Compliance certificates            |                                                         | RoHS                |                                                              |        |
| Logistics data                     |                                                         |                     |                                                              |        |
| Harmonized System (HS) code        |                                                         | 84716070            |                                                              |        |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.